



TRT MIDI

TRINCIATRICI PER TRATTORI
MULCHERS FOR TRACTORS




MADE IN ITALY

TRINCIATRICI TRT MIDI

MULCHERS TRT MIDI



www.meccanicamorellato.it

info@meccanicamorellato.it

049 595 7274



Le **Trinciatrici TRT MIDI** sono adatte alla triturazione di sarmenti, arbusti e rovi di zone incolte, residui erbacei nelle coltivazioni di verdure/ramaglia (fino a 3-4 cm di diametro). Sono macchine robuste e progettate per un lavoro medio/pesante.

- Applicabili a qualsiasi tipo di trattore con attacco a 3 punti cat. I-II
- Telaio robusto in lamiera di acciaio di spessore adeguato
- Sicura grazie alla dotazione di adeguate protezioni a norme CE
- Sabbiatura e verniciatura a polveri in forno
- Garanzia 2 anni



Mulchers TRT MIDI are ideal for sarments, shrubs (max. 3-4 cm diameter) and brambles grinding of untamed areas and weeds residuals from cultivations. They are sturdy and designed for medium/ heavy jobs.

- Can be coupled to any tractor with a 3 points hitch cat. I-II
- Sturdy steel sheet frame of adequate thickness
- Safe thanks to the CE standards protections
- Sandblasting and oven powder coating
- 2 years warranty

Fig. 1 TRT MIDI con spostamento idraulico
TRT MIDI with **hydraulic movement**



Fig. 2 Dettaglio mazze (peso mazza Kg. 1,05)
Hammers detail (Hammer weight 1,05 Kg)



Fig. 3 Dettaglio rullo livellatore autopulente
Self-cleaning levelling roller detail

Fig. 4 Dettaglio rotore con coltelli tripli a Y
Triple Y blades rotor detail




DI SERIE:

Attacco fisso a tre punti cat. I-II (2 posizioni)
Rotore con mazze o coltelli tripli a Y
Sportello apribile per manutenzione
Trasmissione a 2 e 3 cinghie con apposito tenditore
Ruota libera su scatola ad ingranaggi a bagno d'olio
Spinotti per attacco 3 punti
Ingrassaggio dall'esterno del carter cinghie
Slitte e rullo livellatore autopulente regolabili in altezza

STANDARD EQUIPMENT:

Universal 3 points hitch cat. I-II (2 positions)
Rotor with hammers or triple Y blades
Openable bonnet for maintenance
2-3 belts transmission with specific tightener
Free-wheel inserted in the oil-bath gearbox
Pins for 3 points hitch
Rotor bearings greasing without removing the belts case
Skids and self-cleaning levelling roller adjustable in height

MOD.	 (CM)	 (HP)		 (KG)		 (GIRI/MIN.) (RPM)
TRT MIDI 140	137	30-50	28-14	270	2 sez. B	2.500
TRT MIDI 160	157	35-50	32-16	300	2 sez. B	2.500
TRT MIDI 180	172	40-60	36-18	330	3 sez. B	2.500

OPTIONAL:

Kit completo per spostamento idraulico laterale standard (40 cm) Full kit for standard hydraulic side movement (40 cm)
Doppia cassa Double iron sheet frame
Catene (su versione anteriore o posteriore) Chains (on rear or front version)
Set rostri Rear bars set
Versione PTO sinistra (REFORM) Left PTO version (REFORM)
Albero cardanico T4 Cardanic shaft T4
Albero cardanico T5 Cardanic shaft T5