



meccanica  
**Morellato**



# TRT PM

**TRINCIATRICI PER TRATTORI**  
MULCHERS FOR TRACTORS



 MADE IN ITALY

# TRINCIATRICI TRT PM

## MULCHERS TRT PM

www.meccanicamorellato.it  
info@meccanicamorellato.it  
049 595 7274



Le **Trinciatrici TRT PM** sono adatte alla triturazione di sarmenti, arbusti e rovi di zone incolte, residui erbacei nelle coltivazioni di verdure/ramaglia (fino a 3-4 cm di diametro). Sono macchine robuste e progettate per un lavoro medio/pesante.

- Applicabili a qualsiasi tipo di trattore con attacco a 3 punti cat. I-II
- Telaio robusto in lamiera di acciaio di spessore adeguato
- Sicura grazie alla dotazione di adeguate protezioni a norme CE
- Sabbatura e verniciatura a polveri in forno
- Garanzia 2 anni

**Mulchers TRT PM** are ideal for sarments, shrubs (max. 3-4 cm diameter) and brambles grinding of untamed areas and weeds residuals from cultivations. They are sturdy and designed for medium/heavy jobs.

- Can be coupled to any tractor with a 3 points hitch cat. I-II
- Sturdy steel sheet frame of adequate thickness
- Safe thanks to the CE standards protections
- Sandblasting and oven powder coating
- 2 years warranty








**SCOCOA E ROTORE MAGGIORATI**  
THICKER BODY FRAME AND ROTOR

### DI SERIE:

Attacco fisso a tre punti cat. I-II (2 posizioni)  
Rotore con mazze o coltelli tripli a Y  
Sportello apribile per manutenzione  
Trasmissione a 2 e 3 cinghie con apposito tenditore  
Ruota libera su scatola ad ingranaggi a bagno d'olio  
Spinotti per attacco 3 punti  
Ingrassaggio dall'esterno del carter cinghie  
Slitte e rullo livellatore autopulente regolabili in altezza

### STANDARD EQUIPMENT:

Universal 3 points hitch cat. I-II (2 positions)  
Rotor with hammers or triple Y blades  
Openable bonnet for maintenance  
2-3 belts transmission with specific tightener  
Free-wheel inserted in the oil-bath gearbox  
Pins for 3 points hitch  
Rotor bearings greasing without removing the belts case  
Skids and self-cleaning levelling roller adjustable in height

MOD.	 (CM)	 (HP)		 (KG)		PTO (GIRI/MIN.) (RPM)
TRT PM 140	140	35-70	32-16	350	3 Sez. B	2.500
TRT PM 155	155	40-70	32-16	372	3 Sez. B	2.500
TRT PM 170	175	45-80	36-18	395	4 Sez. B	2.500
TRT PM 190	190	55-80	40-20	425	4 Sez. B	2.500
TRT PM 210	210	60-90	44-22	455	4 Sez. B	2.500

### OPTIONAL:

Kit completo per spostamento idraulico laterale standard (40 cm) Full kit for standard hydraulic side movement (40 cm)  
Doppia cassa Double iron sheet frame  
Catene (su versione anteriore o posteriore) Chains (on rear or front version)  
Set rostri Rear bars set  
Versione PTO sinistra (REFORM) Left PTO version (REFORM)  
Albero cardanico T4 Cardanic shaft T4  
Albero cardanico T5 Cardanic shaft T5